



Features

- Treats Iron, Sulfur and Manganese
- Isobar III Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- On demand meter providing data and history
- Adjustable Cycle Times
- High backwash flow capability
- Proprietary two valve bypass with 1" MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- Features Enpress® Vortech™ distributor plate



General Specifications	AF10-3	AF12-3	AF13-3	AF14-3
Filter Media Type	Smart Blend™			
Filter Media Capacity (cu ft)	1.5	2.0	2.5	3.0
Provectr™ AP Tank (polyglass)	10 x 54	10 x 54	10 x 54	16 x 40
Mineral Tanks (Vortech)	10 x 54	12 x 52	13 x 54	13 x 65
Service Flow Rate - Continuous (gpm)	5	6	8	9
Service Flow Rate - Intermittent (gpm)	7	8	10	11
Backwash Flow Rate (gpm)	5.0	6.0	7.0	7.0
Gallons Used / Regeneration	100	120	140	140
Total Space Required Tank	10 X 10 X 62	10 X 12 X 62	10 X 13 X 62	16 X 16 X 73
Approximate Shipping Weight (lbs)	165	236	270	311

